

REPORT OF CHANNEL CONDITIONS
(FOR CHANNELS 400 FEET WIDE OR
GREATER)

Page 1 of 1

Mar-2005

TO:
Florida Inland Navigation District
FL

FROM
USACE, District Engineer
Attn: CESAJ-CO-OM Jacksonville, Florida

RIVER/HARBOR NAME AND STATE
Intracoastal Waterway, Dade, FL

MINIMUM DEPTHS IN EACH 1/4 WIDTH OF
CHANNEL ENTERING FROM SEAWARD

| NAME OF CHANNEL | Date of Survey | AUTHORIZED PROJECT | | | Left Outside Quarter (feet) | Left Inside Quarter (feet) | Right Inside Quarter (feet) | Right Outside Quarter (feet) |
|-----------------|----------------------|--------------------|-------------------|-----------------|--------------------------------------|-------------------------------------|--------------------------------------|---------------------------------------|
| | | Width (feet) | Length (miles) | Depth (feet) | | | | |

| | | | | | | | | |
|---------------------------------------------------------|----------|-----|-----|----|-----|-----|---|-----|
| From Green Daybeacon-11 to the Broad Causeway Bridge | Feb-2005 | 125 | 0.7 | 10 | 3.6 | 2.9 | * | 2.4 |
|---------------------------------------------------------|----------|-----|-----|----|-----|-----|---|-----|

Remarks:

Shoaling located approximately 200 feet south of Red Daybeacon-6A. Shoaling extends across entire channel in the vicinity of Red Nun Buoy-6 and continues southward for approximately 500 feet. Shoaling also along the eastern edge of channel in vicinity of Green Light-9.